

BENCH MODEL DRILL PRESS

- On/off switch located on front of the drill press head for safety
- Spindle is supported by high quality ball bearings
- A 1/2" diameter external positive depth stop with three nut locking feature for quick adjustment
- Adjustable tension spindle return spring
- Rotating ±45° tilting, crank-operated worktable with quick-release clamp
- Hinged metal belt and pulley cover coupled with quick adjustment motor mount allows rapid changing of spindle speeds
- Built-in worklight on all models
- Drill chuck and key included

\$460.⁴⁶

Model:

Stock Number:

Type:

Swing (in):

Drilling Capacity (in):

Chuck Size (in):

Spindle Travel (in):

Spindle Distance to Base (in):

Spindle Distance to Table (max/in):

Table Size (in):

Spindle Taper:

Column Diameter (in):

Number of Spindle Speeds:

Range of Spindle Speeds (RPM):

Overall Height (in):

Base Size (in):

Motor:

Weight (lbs):

JET

JDP-14M

354165

Bench

14

5/8

5/8

3-1/4

24-3/4

18-1/4

12 dia.

MT-2

2-7/8

16

195 - 3,630

40

11-5/8 x 19-5/8

1/2 HP, 1 Ph

115/230v Prewired 115v

132



S14 DRY CUTTING SAW

- Utilizing a 14" carbide tipped blade, the Steelmax S14 cuts through metal faster, safer and cleaner than abrasive chop saws in a fraction of the time and cost.
- Powered with a 15 amp motor and geared to turn slower than a chop saw, the S14 dry cutter cuts like a cold saw.
- Sold standard with a 14" carbide tipped mild steel blade attached, heavy duty, industrial strength cast iron base and two position locking vise, this saw is ready for immediate action!
- Cuts solid mild steel up to 1" thickness; cut profiles: pipe, angles, channel with a depth of cut up to 4-3/4". Bevels to 45 degrees.
- Saves time and money giving cool cuts that need little to no finishing, eliminating any need for grinding or cool down time.

14" BLADES

14" Dia. Blade x 1" Arbor

66 Teeth x 1450 RPM

Cuts Mild Steel

(less than 1" thick)

RGMBL-014

\$109.95

14" Dia. Blade x 1" Arbor

90 Teeth x 1450 RPM

Cuts Stainless Steel

(less than 1/4" thick)

RGMBL-014SS

\$164.95



\$599.⁹⁵

HORIZONTAL / VERTICAL BANDSAWS

HVBS-463

- Ball bearing supported blade wheel
- Adjustable ball bearing guides
- Heat-treated steel worm gear and bronze drive gear
- Automatic shut-off after cut
- Shelf built into stand
- STANDARD EQUIPMENT
- Vertical worktable
- Rear wheels attached to stand
- Adjustable material stop

JET



Model:

Stock Number:

Round Capacity at 90° (in):

Round Capacity at 45° (in):

Rectangle Capacity at 90° (in):

Rectangle Capacity at 45° (in):

Throat Depth (in):

Vertical Worktable (in):

Vise Swivels:

Blade Size (in):

Blade Wheel Diameter (in):

Blade Speeds (SFPM):

Bed Height (in):

Floor Space Required (in):

Motor:

Net Weight (lbs):

HVBS-463

414458

4

3

4 x 6

4 x 3

5

9-5/8 x 9-1/2

45°

1/2 x 0.025 x 64-1/2

7-3/8

80, 120, 200

24

16-1/4 x 42-1/2

1/2 HP, 1 Ph, 115/230v, Prewired 115v

110

4" x 6" CAP.

\$436.⁴⁶

HVBS-7MW

- UL listed motor
- Automatic shut-off after cut
- Heavy cast iron bow and bed
- Roller cabinet with built-in chip tray
- Hardened and ground worm gear
- Adjustable roller blade guides
- STANDARD EQUIPMENT
- Complete coolant system
- Vertical worktable
- Chip brush
- Adjustable material stop
- Bi-metal 5/8 T.P.I. saw blade

JET



Model

Stock Number:

Round Capacity of 90° (in):

Round Capacity at 45° (in):

Rectangle Capacity at 90° (in):

Rectangle Capacity at 45° (in):

Throat Depth (in):

Vertical Worktable (in):

Vise Swivels:

Blade Size (in):

Blade Wheel Diameter (in):

Blade Speeds (FPM):

Bed Height (in):

Floor Space Required (in):

Motor (UL Listed):

Net Weight (lbs):

HVBS-7MW

414459

7

4-1/2

2 x 12 - 7 x 8-1/2

7 x 5

7

9-3/8 x 10

45°

3/4 x 0.032 x 93

11-3/4

85, 130, 180, 285

23

20-1/2 x 49-1/2

3/4 HP, 1 Ph, 115/230v, Prewired 115v

318

7" x 8-1/2" CAP.

\$1099.⁰⁰