

### Welded Rings

- Made of low carbon material for general chain attachment
- May also be used with cable or rope
- *Do Not Use For Overhead Lifting*

**Campbell®**



INSIDE DIA.	BODY DIA.	WORKING LOAD LIMIT	FINISH	ITEM #	PRICE
1-1/4"	3/16"	200 lbs.	Bright	605-0314	.82
1-1/2"	1/4"	450 lbs.	Bright	605-0414	.88
2"	5/16"	900 lbs.	Bright	605-0614	1.86
3"	3/8"	900 lbs.	Galv	605-3614	2.26

### Pad Eyes

- Widely used on farm machinery, trucks, steel hulled marine vessels and material handlers
- Standard Material: Drop-forged C-1038 carbon steel



**Campbell®**

SIZE	HOLE DIA.	OUTSIDE DIA.	PAD DIA.	ITEM #	PRICE
1-1/2	5/8"	1-1/8"	1"	710-5301	\$3.20
2	3/4"	1-1/2"	1-1/16"	710-5302	3.20
4	1"	2-1/8"	1-7/16"	710-5303	7.12
5	1-1/4"	2-5/8"	1-3/4"	710-5304	10.78

### Eye Nuts

- Standard Material: Drop-forged carbon steel
- Standard Finish: Galvanized to ASTM A-153 specifications
- Design Factor: 5 to 1



**Campbell®**

TRADE #	WORKING LOAD LIMIT	THREAD SIZE	INSIDE WIDTH	ITEM #	PRICE
1A	850 lbs.	5/16"-18	3/4"	710-0102	\$7.94
2	1250 lbs.	3/8"-16	1"	710-0103	8.70
3	1650 lbs.	7/16"-14	1-1/4"	710-0104	8.60
3A	2250 lbs.	1/2"-13	1-1/2"	710-0105	10.04

### Lifting Clamps

- Can be used for both vertical and horizontal-to-vertical lifting
- Shackle and "G" link combined into one part for fewer stress points and less chance of side loading damage
- "GX" clamp is entirely drop forged and heat treated
- Exclusive feature is a patented wear indicator system. When any of cam's straight line, convex teeth are flattened between unique wear indicator grooves, it is time to change the cam
- 100% proof tested with certificate of test attached to each clamp



**Campbell®**

GRIP RANGE	WORKING LOAD LIMIT	CLAMP WEIGHT	ITEM #	PRICE
1/16" - 5/8"	1/2 ton	4 lbs	642-3000	\$337.02
1/16" - 3/4"	1 ton	8 lbs	642-3005	478.72

### Quick-Alloy Coupling Links

1. Loop one half through attachment, the other through chain. Fit together.
2. Place stud assembly and alloy locking pin in link.
3. Drive the locking pin in until the snapping engages the recessed portion of the pin




**Campbell®**

CHAIN SIZE	INSIDE DIA.	WORKING LOAD LIMIT	ITEM #	PRICE
7/32"	17/64"	2100 lbs.	577-0315	\$16.04
9/32"	5/16"	3500 lbs.	577-9125	18.48
3/8"	7/16"	7100 lbs.	577-9135	21.24
1/2"	5/8"	12,000 lbs.	577-9145	34.52

### Double Clevis

- Forged, heat treated and tempered
- For use with System 4 chain
- Standard Finish: Blu-Krome



**Campbell®**

FOR CHAIN SIZE	WORKING LOAD LIMIT	LINK GAP	PIN DIA.	ITEM #	PRICE
1/4" & 5/16"	3900 lbs.	7/16"	3/8"	T542-3300	\$7.10
3/8"	5400 lbs.	1/2"	7/16"	T542-3301	8.62
7/16" & 1/2"	9200 lbs.	5/8"	9/16"	T542-3302	14.40

### Latched Swivel Hoist Hooks - Alloy

- Standard Finish: Painted orange and stamped "Alloy"
- Latched swivel hoist hook
- Standard material: Alloy steel
- Standard finish: Painted orange
- Design factor: 4 to 1
- Other features: All hooks are drilled for latch kits



**Campbell®**

CHAIN SIZE	WORKING LOAD LIMITS	HOLE DIA.	ITEM #	PRICE
#3	2,000 lbs.	1-1/2"	395-2315	\$40.68
#5	4,000 lbs.	1-1/2"	395-2515	63.42
#7	9,000 lbs.	1-3/4"	395-2715	87.90

### Fist Grip Drop Forged Cable Clamps

- Standard Material: Base is drop-forged carbon steel, with heavy hex nuts
- Unlike U-bolt type rope clamps, Fist Grip clamps cannot be installed incorrectly with the saddle not on the live rope end.
- Standard Finish: Galvanized to meet ASTM A-153 specifications



CABLE SIZE	TORQUE FOOT LBS.	MIN. CLAMPS REQUIRES	ITEM #	PRICE
7/16" 1/2"	65	3	1GRPF4450X	\$6.62
9/16" 5/8"	130	3	1GRPF5663X	8.75